MOBILE-ID
Anytime, Anywhere

Dot Matrix Printer **2600+**

High performance at low cost



Highlights at a glance:

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 80 columns / A4
- 24 wires print head for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- USB Host interface for easy firmware-update
- User-friendly, backlit illuminated LC display

2600+

The new Dot Matrix Printer 2600+ is the further developed variant of the successful Dot Matrix Printer 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A metal tear bar ensures that even thicker paper or multiple sets are separated cleanly. The durable ribbon for 10 million characters can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces USB, Parallel and Ethernet (with IPv6 support), the Dot Matrix Printer 2600+ now also has a USB host interface, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only up to 20% faster, but also allows for a noise reduction of up to 2 decibels thanks to its design.

TECHNICAL DATA

Print speed	Fastest Speed: Character density HS Draft Draft NLQ LQ	683 cps 10 / 12 / 15 cpi 600 / 683 / 683 cps 513 / 513 / 513 cps 228 / 273 / 171 cps 114 / 137 / 171 cps
Resolution	Up to360 × 360 dpi	
Throughput (ECMA 132)	457 pages per hour	
Character density	10, 12, 15, 17.1, 20 cpi	
Line density	2, 3, 4, 6, 8, 12 lpi	
Print Head Life	500 Mio. impact per wire	
RAM	256 kB	
Interface Standard	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6), USB Host	
Interface Optional	Serial RS-232	
Administration	Tally WebPanel via Ethernet; Config-Tool via USB/Parallel	
Emulations Standard	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9-Nadel Emulation **LA Upgrade Kit**: DEC PPL2	
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing	
Consumables	Ribbon: 10 Mio. characters	

Paper handling Standard	One tractor usable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
Paper handling Optional	Additional push tractor (rear)
Copies	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies
Paper types	Cut sheets, continuous forms, multi-part forms
Paper weight	60-120 g/m²
Paper format	Width: 76 to 278 mm; Length: 76 to 599 mm
Weight	8,1 kg
Dimensions	458 × 265 × 200 mm (W x D x H)
Noise	<53 dB(A)
Voltage	100 - 240 V autosensing
Power consumption	60 Watt printing; <3 W Sleep Mode
Temperature	+10° to +40° C; 10% to 85% rel. humidity
Print volume	20.000 pages per month
MTBF	25.000 hours @20% duty cyle
Driver	Windows 8/8.1/10/11 and Server2012/2016/2019/2022; SAP
Warranty	For more details please contact your local dealer

Configuration: **2600+** Standard model

MOBILE-ID
Anytime, Anywhere
Mobile-ID Technologies and Services Joint Stock Company

www.mobile-id.vn
info@mobile-id.vn
1900 6884